
## **KEMET Part Number: MPXV1D0520LR68**

(UPI2X10520VR68)



## KEMET, MPXV, Power, 0.68 uH, 20%, 0520(2120)



Dimensions		
L	5.3mm +/-0.2mm	
W	5mm +/-0.2mm	
Т	2mm MAX	
LL	1mm NOM	
G	2.5mm +/-0.2mm	

Packaging Specifications		
Packaging:	T&R, 330mm	
Packaging Quantity:	3500	

General Information		
Series:	MPXV	
Style:	SMD	
Chip Size:	0520(2120)	
Description:	Surface Mount Inductor	
Features:	Power Inductors	
RoHS:	Yes	
Qualifications:	AEC-Q200	
AEC-Q200:	Yes	
Core:	Composite	
Miscellaneous:	40 (K) Temperature Rise Max.	

Specifications		
Inductance:	0.68 uH (100 KHz)	
Inductance Tolerance:	20%	
Temperature Range:	-55/+155°C	
Shielded:	Yes	
Current:	9.5 A (Irms, 40C Rise By Self Heating), 7.5 A (Isat, 20% Drop In Inductance), 11 A (Isat, 30% Drop In Inductance)	
DC Resistance:	12.2 mOhms	
Self-Resonant Frequency:	74 MHz	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

